



Ref. Certif. No.

DK-144440-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	I.T.E. POWER SUPPLY
Name and address of the applicant	BRIDGEPOWER CORP (Gosaek-dong) 16 Omokchen-ro 132beon-gil Gwonseon-gu Suwon-si, Gyeonggi-do, 441-813 Republic of Korea
Name and address of the manufacturer	SL POWER ELECTRONICS CORP 27001 Agoura Rd. Suite 325 Calabasas, CA 91301 United States
Name and address of the factory	BRIDGEPOWER CORP (Gosaek-dong) 16 Omokchen-ro 132beon-gil Gwonseon-gu Suwon-si, Gyeonggi-do, 441-813 Republic of Korea Additional Information on page 2
<i>Note: When more than one factory, please report on page 2</i>	
Ratings and principal characteristics	Input: 100-240 Vac, 50-60 Hz, 2.0 A (2.0 A-0.8 A) Additional Information on page 3
Trademark / Brand (if any)	N/A
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	BIP150SXXX, BIP150AXXX, NGB150SXXXXXX, NGB150AXXXXXX Additional Information on page 2
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to: EN IEC 62368-1:2020, EN IEC 62368-1:2020/A11:2020 National Differences: EU Group Differences, CA, CN, GB, US Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	E300305-S23O-044-1 issued on 2023-08-08

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-08-23

Signature: Thomas Wilson



Ref. Certif. No.

DK-144440-UL

Factory(ies):

WENDENG JEIL ELECTRONICS CO LTD
Xiamen Road NO.2 Wendeng Economic Development Zone Weihai City, Shandong,
China

BRIDGEPOWER VINA Company Limited
Lot B9 Thuy Van Industrial Zone Viet Tri, Phu Tho,
Vietnam

Additional Model Detail(s):

BIP150AXXX, B I P 1 5 0 A XX X
(1) (2) (3)

- (1) S: With Auxiliary Power board
A: No Auxiliary Power board
- (2) XX = Output Voltage (12, 15, 19, 24, 48)
- (3) X = Input Connector Opions (C)
C : Class II Connector type

BIP150SXXX, B I P 1 5 0 S XX X
(1) (2) (3)

- (1) S: With Auxiliary Power board
A: No Auxiliary Power board
- (2) XX = Output Voltage (12, 15, 19, 24, 48)
- (3) X = Input Connector Opions (C)
C : Class II Connector type

NGB150AXXXXX, N G B 1 5 0 A XX X XX
(1) (2) (3) (4)

- (1) S: With Auxiliary Power board
A: No Auxiliary Power board
- (2) XX = Output Voltage (12, 15, 19, 24, 48)
- (3) X = Input Connector Options (C)
C : Class II Connector type

NGB150SXXXXX, N G B 1 5 0 S XX X XX
(1) (2) (3) (4)

- (1) S: With Auxiliary Power board
A: No Auxiliary Power board
- (2) XX = Output Voltage (12, 15, 19, 24, 48)
- (3) X = Input Connector Options (C)
C : Class II Connector type
- (4) XX = Number : Blank or 00 thru 99

Additional information (if necessary)



- UL Solutions (US), 333 Pflugsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-08-23

Signature:

Thomas Wilson



Ref. Certif. No.

DK-144440-UL

Additional Ratings:

Output:

- 12 Vdc , 10.0 A (for CONVECTION mode),
- 12 Vdc , 12.50 A (for 200LFM mode)
- 15 Vdc , 8.0 A (for CONVECTION mode),
- 15 Vdc , 10.0 A (for 200LFM mode)
- 19 Vdc , 6.32 A (for CONVECTION mode),
- 19 Vdc , 7.90 A (for 200LFM mode)
- 24 Vdc , 5.0 A (for CONVECTION mode),
- 24 Vdc , 6.25 A (for 200LFM mode)
- 48 Vdc , 2.5 A (for CONVECTION mode),
- 48 Vdc , 3.13 A (for 200LFM mode)
- STANDBY OUTPUT: 5 Vdc , 0.5 A
- FAN OUTPUT: 12 Vdc , 0.4 A

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-08-23

Signature:

Thomas Wilson