



Ref. Certif. No.

DK-144011-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

| | |
|---------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product | Component power supply |
| Name and address of the applicant | BRIDGEPOWER CORP (Gosaek-dong) 16 Omokchen-ro 132beon-gil Gwonseon-gu Suwon-si, Gyeonggi-do, 441-813 Republic of Korea |
| Name and address of the manufacturer | SL POWER ELECTRONICS CORP 27001 Agoura Rd. Suite 325 Calabasas, CA 91301 United States |
| Name and address of the factory | BRIDGEPOWER CORP (Gosaek-dong) 16 Omokchen-ro 132beon-gil Gwonseon-gu Suwon-si, Gyeonggi-do, 441-813 Republic of Korea <input checked="" type="checkbox"/> Additional Information on page 2 |
| <i>Note: When more than one factory, please report on page 2</i> | |
| Ratings and principal characteristics | Input: 100-240 V~, 50-60 Hz, 2.0 A (2.0 A - 0.8 A) <input checked="" type="checkbox"/> Additional Information on page 2 |
| Trademark / Brand (if any) | None |
| Customer's Testing Facility (CTF) Stage used | |
| Model / Type Ref. | NGB150(1)(2)(3)(4), BIP150(1)(2)(3) <input checked="" type="checkbox"/> Additional Information on page 2 |
| Additional information (if necessary may also be reported on page 2) | Additionally evaluated to: EN 60601-1:2006, EN 60601-1:2006/A1:2013, EN 60601-1:2006/A12:2014, EN 60601-1:2006/A2:2021 National Differences: EU Group Differences, CA, US The risk management requirements of the standard were not addressed <input type="checkbox"/> Additional Information on page 2 |
| A sample of the product was tested and found to be in conformity with | IEC 60601-1:2005, IEC 60601-1:2005/AMD1:2012, IEC 60601-1:2005/AMD2:2020 |
| As shown in the Test Report Ref. No. which forms part of this Certificate | E302267-D1060-1/A0/C0-CB issued on 2023-08-04 |

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-08-10

Signature: Thomas Wilson



Ref. Certif. No.

DK-144011-UL

Factory(ies):

WENDENG JEIL ELECTRONICS CO LTD
Xiamen Road NO.2 Wendeng Economic Development Zone Weihai City, Shandong,
China

BRIDGEPOWER VINA Company Limited
Lot B9 Thuy Van Industrial Zone Viet Tri, Phu Tho,
Vietnam

Additional Model Detail(s):

BIP150(1)(2)(3), (Where (1) can be S or A, (2) can be 12 to 48, (3) can be C)
(1) can be S or A for Model Configuration. S: Sub-board, A: No Sub-board
(2) can be 12 for 12 Vdc, 15 for 15 Vdc, 19 for 19 Vdc, 24 for 24 Vdc or 48 for 48 Vdc Output Voltage.
(3) can be C for input plug type. C: Class II= Connector type

NGB150(1)(2)(3)(4), (Where (1) can be S or A, (2) can be 12 to 48, (3) can be C, (4) can be Blank or 00 thru 99.)
(1) can be S or A for Model Configuration. S: Sub-board, A: No Sub-board
(2) can be 12 for 12 Vdc, 15 for 15 Vdc, 19 for 19 Vdc, 24 for 24 Vdc or 48 for 48 Vdc Output Voltage.
(3) can be C for input plug type. C: Class II= Connector type
(4) can be blank or 00 thru 99 for Model Configuration.

Additional Ratings:

Output:
+12 Vdc, 10.0 A (For convection)/+12 Vdc, 12.5 A (For 200 lfm) or
+15 Vdc, 8.0 A (For convection)/+15 Vdc, 10.0 A (For 200 lfm) or
+19 Vdc, 6.32 A (For convection)/+19 Vdc, 7.9 A (For 200 lfm) or
+24 Vdc, 5.0 A (For convection)/+24 Vdc, 6.25 A (For 200 lfm) or
+48 Vdc, 2.5 A (For convection)/+48 Vdc, 3.13 A (For 200 lfm),
Standby output: +5 Vdc, 0.5 A,
Fan output: +12 Vdc, 0.4 A

Additional information (if necessary)



- UL Solutions (US), 333 Pflingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-08-10

Signature:

Thomas Wilson